





PRECISION & FLEXIBILITY FOR EVERY BIG IDEA

Large Format Personalization with Speed & Smart Automation



A1- Size 60 x 90 cm Print Area

Create larger designs for big ideas



Faster Printing Speeds

3.6X faster speeds compared to conventional systems



Up to 25 cm Print Height

Aligned with laser and CNC machine heights



Smarter Material Handling

Height differences of up to 6 mm, ideal for textured or uneven surfaces.



Enhanced Print Quality

Ultra-high-resolution prints with 1800 DPI precision.



Flat-Rotary Quick Switch

Easily switch to rotary printing, 1.5cm-22cm in diameter



3D & ADA Braille Accessibility

Precision-crafted Braille dots & embossed touchable colors



Advanced Varnish Printing

Add depth & premium feel with gloss or matte effect



CMYK + WW + VV at One Pass

Enables multi-color and specialty ink printing in a single pass.

APPLICATIONS - FLEXIBILITY FOR ANY CHALLENGE



360 Rotary Personalization







Cards Luggage

Corporate Gifts


Signage & Braille















126 cm (49.60 in)

5 font size abcdefghijklmopqrstu 6 font size abcdefghijklmop 7 font size abcdefghijk 8 font size abcdefg 9 font size abo **Fine Detail**



Ordering Information

Printer name Goods No.

artisJet Trust

AJTT-3200

DTS UV LED Curing Vertical Loading Ink Cartridges

Ink Type **Ink Channels**

CMYK+WWWW/CMYK+WW+VV

230 gr Ink Cartridges

Cvan UV-LED Ink DTSAT3 For Freebird, 230g Magenta UV-LED Ink DTSAT3 For Freebird, 230g Yellow UV-LED Ink DTSAT3 For Freebird, 230g Black UV-LED Ink DTSAT3 For Freebird, 230g White UV-LED Ink DTSAT3 For Freebird, 230g

DTSAT3-UV10-C-02 DTSAT3-UV10-M-02 DTSAT3-UV10-Y-02 DTSAT3-UV10-K-02 DTSAT3-UV10-W-02

On Demand Varnish

Varnish UV-LED Ink DTSAT3 For Freebird, 230a

DTSAT3-UV10-V-02

Cleaning agent Fixing agent

500 ml AJCA-U-500-001 500 ml AJCP-U-500-001



Printing Specifications

Supporting Applications Compatible Materials Signage, wall Decor, trophies and awards, packaging, corporate gifts, small items batch production, luggage, bottle and cylindrical items etc. Precise and stable material handling due to vacuum table flexibility, covering diverse substrates, including curved, uneven surfaces, and heat-sensitive substrates: wood, MDF, aluminum, stainless steel, plastic, acrylic, leather, candles, cardboard etc

Printing Size Area Printing Height Al+ print area, 600 x 900 mm (23.62 x 35.43 in) Full Automatic Height Measurement up to 25 cm (9.84 in)

Printing Speed

~10 minutes for Full 60x90CM @ 720x1800 DPI for KCMY bidirectional print mode

Printing Resolution

1800 DPI ultra-high resolution prints

Epson i3200 piezo electric printhead. Made in Japan

Built-in Printing Technology Flat to 360 Rotary Quick Switch

UV LED curing technology with Advanced FREEBIRD Print Engine powered by advanced chips and firmware

Rotary Print Diameter

Industrial-Grade Aviation Connection Port and servo-motor driven ROT 360 system

Clean Print Module (Optional)

Thinner Section of Rotary Device from 15 mm to 35 mm: Wider Section of Rotary Device from 35 mm to 220 mm

Print Head

Increase material preparation efficiency by 85%, especially effective in winter and dry weather condition

Printer Specifications

Nozzles

8 Chambers; 360*8 nozzles

Interface Connectivity Operating System

USB 2.0 / 3.0 Windows®

Printer Dimensions (D*W*H)

 $Printer 1430 \times 1260 \times 835 \ mm \ (56.30 \times 49.60 \times 32.87 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 1310 \times 980 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping 1480 \times 38.58 \ mm \ (58.27 \times 51.57 \times 38.58 \ in); Shipping$

Printer Weight Available Systems

Printer 240 Kg, Shipping 308 Kg

White Ink Circulation, Intelligent Air UV Cooling System, Magnetic Encoding, Intelligent Ink Cleaning Estimation, Vacuum Table with Flexible Zones, Auto-Height Measurement with Advanced Precision Sensors

Content of the Box

artisJet Trust, USB cable, Power cable, User manual book, spare parts package,

SCM Cable, RIP Software, Extra back-up Damper

Environmental Ranges

50°F to 95°F (10°C to 35°C) A110-220V, 50 Hz-60 Hz max 3.0A

Power Input Global Compliance

CE/FCC/RoHS/REACH/HC/RCM/FDA/UL/RISC/CCC/BIS/UKCA certified

Warranty

Software

2 vears

artisRIP V9.0

Layout editing platform, resize, mirror, text, color adjustment, color gamut check; Raster and vector images support; Built in customizable card print templates; Previewing and smart nesting.

artislet Workstation

Workflow Integration: HOT-FOLDER automation and REAL-TIME monitoring, streamlining production processes & reducing operator workload.

Product- based & Effect-based Virtual Printer: Create dedicated virtual printers for specific products and templates or batch production. Open API for Automation: Equipped with an Open API for advanced automation and integration.

Preview of Print Effects & Job Identification: Real time preview of the print effects, including color accuracy, ink coverage, & design alignment.

Ink Cost Control & Time Management: Real-time estimation of printing costs and prediction of printing time optimizing production planning. Ink Capacity Pre-Estimation: Calculates the remaining ink capacity and estimates whether it is sufficient to complete the current job. One Print Head + One Go = 10 Print Effects: White+Color (2 White channels), White+Color Edge Adjusted, White+Color 2 White Layers, CWV, C+V, V+C, CWC, White+Color (Spot Color), WCV (Spot Color Letter-based Edge Sharpening: Offers adjustable edge sharpening degrees for text and lettering, enhancing clarity and definition.

Copies to Print in One Click: Specify the number of copies to print with a single click, streamlining repetitive tasks. Self-Maintenance System: Reduces the need for daily cleaning by automating routine maintenance during idle periods.

3rd Party Software Compatibility

Empowered by HOT FOLDER Technology, artisJet Workstation allows users to print directly from their preferred design software, being fully compatible with a wide range of third party software, including Adobe Illustrator, CorelDRAW, and Adobe Photoshop.



























SCAN TO VISIT PRODUCT PAGE





